

TECHNICAL DATA SHEET

Contact protective coating

Art. no. 0893 70

P. Qty.: 1 / 12

Transparent spray protective lacquer

Prevents or rectifies soft shorts on coils and transformers. Protects against moisture, diluted acids/alkalis, water and corrosion by forming a shiny, flexible film. Adheres to metals such as copper, brass, steel, chrome and aluminium.

Contents	200 ml
Density	0.839 g/cm ³
Density conditions	at 20 °C



Application area

Seals all kinds of electrical cables. Insulates, seals, protects wiring and connectors from corrosion and contamination.

Application information

Apply from a distance of approximately 25 cm at room temperature by spraying the corresponding, previously cleaned surface.

Notice

Contact SL must be completely dry before the electrical system is restarted. Do not work while energised. The product is highly flammable. Container is pressurised. Protect from sunlight and temperatures over 50 °C. Turn the can upside down and spray after use. Before application, check product for material compatibility.

The usage instructions are recommendations based on the tests we have conducted and our experiences; test the product before each application. We do not assume any liability for a specific application result due to the large number of applications and storage/usage conditions. Insofar as our free customer service provides technical information or acts as an advisory service, this service is provided under the exclusion of any liability, unless the advice or information given falls within the scope of our specified, contractually agreed scope of services or the consultant was acting deliberately. We guarantee consistent quality of our products. We reserve the right to make technical changes and carry out further development.