

TECHNICAL DATA SHEET

Winter diesel performance improver

Art. no. 5861 002 150

P. Qty.: 1 / 12

To improve the filterability and the cloud point of diesel fuel

Contents	150 ml
Colour	Transparent, translucent, opaque
Smell/fragrance	Characteristic
Chemical basis	Combination of additives
Shelf life from production	60 Month
Density	0.813 g/cm ³
Density conditions	at 20 °C
Min. flashing point	63 °C



Application area

For all passenger car and truck diesel engines, buses, construction machinery, including common rail and pump/nozzle systems.

Notice

The additive must be added before the first flocculation; any flocculation that has already occurred cannot be dissolved by the product. Ideally, the additive should be at room temperature and the diesel fuel being treated should not be below 0 °C. The additive should ideally be added just before the fuelling process.

The usage instructions are recommendations based on the tests we have conducted and our experience; carry out your own tests before each application. Due to the large number of applications and storage and processing conditions, we do not assume any liability for a specific application result. Insofar as our free customer service provides technical information or acts as an advisory service, no responsibility is assumed by this service except where the advice or information given falls within the scope of our specified, contractually agreed service or the advisor was acting deliberately. We guarantee consistent quality of our products. We reserve the right to make technical changes and further develop products.